

CLAIMS

What is claimed is:

- 1 1. A method for utilizing an interface client in an interface roaming network,  
2 comprising:
  - 3 (a) submitting information about an interface client to a wireless link in vicinity  
4 to the interface client;
  - 5 (b) receiving content; and
  - 6 (c) displaying the content on a display of the interface client.
- 1 2. The method of claim 1, further comprising receiving a signal from the  
2 wireless link when the wireless link is in the vicinity of the interface client  
3 prior to submitting the information about the interface client to the wireless  
4 link.
- 1 3. The method of claim 2, wherein the signal from the wireless link is  
2 transmitted from the wireless link in response to a prior signal transmitted  
3 from the interface client.
- 1 4. The method of claim 2, wherein the signal from the wireless link includes  
2 information identifying a user of the wireless link.
- 1 5. The method of claim 1, wherein the information about the interface client  
2 includes at least one of: information about the capabilities of the interface  
3 client, information about display capabilities of the interface client,  
4 information about an input device of the interface client, and information  
5 about the location of the interface client.
- 1 6. The method of claim 1, wherein the content is received from an infrastructure  
2 server.

- 1 7. The method of claim 6, wherein the content is received from the  
2 infrastructure server via the wireless link.
- 1 8. The method of claim 1, wherein the content is formatted based on the  
2 submitted information about the interface client.
- 1 9. A system for utilizing an interface client in an interface roaming network,  
2 comprising:  
3 an interface client adapted for submitting information about the  
4 interface client to a wireless link in vicinity to the interface client; and  
5 the interface client having a display adapted for displaying content  
6 received by the interface client.
- 1 10. The system of claim 9, wherein the interface client has a transceiver adapted  
2 for receiving a signal from the wireless link when the wireless link is in the  
3 vicinity of the interface client prior to submitting the information about the  
4 interface client to the wireless link.
- 1 11. The system of claim 10, wherein the signal from the wireless link is  
2 transmitted from the wireless link in response to a prior signal transmitted  
3 from the transceiver of the interface client.
- 1 12. The system of claim 10, wherein the signal from the wireless link includes  
2 information identifying a user of the wireless link.
- 1 13. The system of claim 9, wherein the information about the interface client  
2 includes at least one of: information about the capabilities of the interface  
3 client, information about display capabilities of the interface client,  
4 information about an input device of the interface client, and information  
5 about the location of the interface client.

1 14. The system of claim 9, wherein the content is received from an infrastructure  
2 server.

1 15. The system of claim 14, wherein the content is received from the  
2 infrastructure server via the wireless link.

1 16. The system of claim 9, wherein the content is formatted based on the  
2 submitted information about the interface client.

1 17. A computer program product for utilizing an interface client in an interface  
2 roaming network, comprising:

- 3 (a) computer code for submitting information about an interface client to a  
4 wireless link in vicinity to the interface client;  
5 (b) computer code for receiving content; and  
6 (c) computer code for displaying the content on a display of the interface client.

1 18. The computer program product of claim 17, wherein the information about  
2 the interface client includes at least one of: information about the capabilities  
3 of the interface client, information about display capabilities of the interface  
4 client, information about an input device of the interface client, and  
5 information about the location of the interface client.

1 19. The computer program product of claim 17, wherein the content is received  
2 from an infrastructure server via the wireless link.

1 20. The computer program product of claim 17, wherein the content is formatted  
2 based on the submitted information about the interface client.